

GC1380



Description

High sensitivity 1.4 Megapixel CCD camera with GigE Vision

The ultra-compact 1.4 Megapixel GC1380 is a very sensitive, high-resolution CCD camera with Gigabit Ethernet interface (GigE Vision®). The GC1380 incorporates the incomparable Sony ICX285 CCD sensor with ExView technology providing high-sensitivity, low noise, excellent antiblooming, and superb image quality. The GC1380 runs 20 frames per second at 1360x1024 resolution and even faster with region of interest readout.

- Sony ICX285 2/3" ExView Progressive scan CCD
- High resolution - 1.4 megapixel (1360x1024)
- Exceptional image quality
- **Models:**
 - GC1380, 1360x1024, 20 fps, CCD, mono
 - GC1380C, 1360x1024, 20 fps, CCD, color



Important information: [Prosilica GC Power Voltage Specification Update](#)

Specifications

Prosilica GC		1380
Interface	IEEE 802.3 1000baseT	
Resolution	1360 x 1024	
Sensor	Sony ICX285	
Type	CCD Progressive	
Sensor Size	Type 2/3	
Cell size	6.45 μ m	
Lens mount	C	
Max frame rate at full resolution	20 fps	
A/D	12 bit	
On-board FIFO	16 MB	
Output		
Bit depth	8/12 bit	
Mono modes	Mono8, Mono12Packed, Mono16	
Color modes YUV	YUV411, YUV422, YUV444	
Color modes RGB	RGB24, BGR24, RGBA24, BGRA24	
Raw modes	Bayer8, Bayer12Packed, Bayer16	
General purpose inputs/outputs (GPIOs)		
TTL I/Os	1 input, 1 output	
Opto-coupled I/Os	1 input, 1 output	
RS-232	1	
Power/Mass/Dimensions/Regulations		
Power requirements (DC)	5-16 V*	
Power consumption (12 V)	3.3 W	
Mass	104 g	
Body Dimensions (L x W x H in mm)	59x46x33 including connectors, w/o tripod and lens	
Regulations	CE, FCC, Class A, RoHS	

* Cameras shipped after April 1, 2011 support 5-25 VDC. Please review the [Prosilica GC Power Voltage Specification Update](#) for further information.

[Download Prosilica GC1380 technical drawing \(click here\)](#)



Smart features

The GC1380 features include:

- Auto Exposure
- Auto Gain
- Auto White balance
- Flexible Binning
- Region of Interest readout (AOI partial scan)
- StreamBytesPerSecond (easy bandwidth control)
- Stream hold
- Asynchronous external trigger and sync I/O
- Global shutter (digital shutter)
- Recorder and Multiframe Acquisition Modes

Applications

The GC1380 is ideal for a wide range of applications including:

- industrial inspection
- machine vision
- ophthalmology
- aeronautical and aerospace
- public security
- surveillance
- traffic imaging
- OEM applications

Application Case Study:

- **Prosilica GC GigE Camera in Coral Reef Fish Study**

Science & Research: Prosilica GC GigE Vision Cameras used by research team of New Jersey Institute of Technology to assess population of endangered fish species in coral reefs.

- **Coming to a street near you**

Prosilica GC1380C camera captures images for Microsoft Bing Maps Streetside.